

General Specifications

Parameter	6dB	10dB	15dB	20dB
Norm Ops Freq (MHz)	800 ~ 2500 MHz	800 ~ 2500 MHz	800 ~ 2500 MHz	800 ~ 2500 MHz
Max Ops Freq (MHz)	3000 MHz	3000 MHz	3000 MHz	3000 MHz
VSWR on Main Line	1.2:1 typ.	1.2:1 typ.	1.2:1 typ.	1.2:1 typ.
VSWR on Sec. Line	1.3:1 typ.	1.3:1 typ.	1.3:1 typ.	1.3:1 typ.
Insertion Loss (dB)	1.6 dB typ.	0.7 dB typ.	0.3 dB typ.	0.3 dB typ.
Coupling Loss (dB)	6.5 dB typ.	10.2 dB typ.	15.3 dB typ.	20.2 dB typ.
Isolation (dB)	30 dB typ.	30 dB typ.	30 dB typ.	30 dB typ.
Power Handling	200 W	200 W	200 W	200 W
Impedance (ohm)	50 ohm	50 ohm	50 ohm	50 ohm
Dimension	See diagram below	See diagram below	See diagram below	See diagram below
Weight	≈ 80g	≈ 80g	≈ 80g	≈ 80g
Connector	N type	N type	N type	N type
Operation Temperature	-35°C ~ +65°C	-35°C ~ +65°C	-35°C ~ +65°C	-35°C ~ +65°C
Operation Humidity	5 ~ 95%	5 ~ 95%	5 ~ 95%	5 ~ 95%

